

Visit [VacuumInterrupterTesting.com](http://VacuumInterrupterTesting.com)  
to download our technical paper  
on predicting the remaining life  
of vacuum interrupters in the field.



# WHEN PASS-FAIL ISN'T ENOUGH

## Trust Magnetron Atmospheric Condition (MAC) testing to predict the remaining life of your vacuum interrupters

Until now, the accepted field service test for vacuum interrupters has been a simple go/no-go test performed with an AC high-potential test. Today, testing with our Magnetron Atmospheric Condition (MAC) test sets can prevent unnecessary damage to your circuit breakers and contactors.

US PATENT NO. 9,031,795 B1

### THIRD-GENERATION MAC-TS4 VACUUM INTERRUPTER TEST SET NOW WORKS WITH YOUR PC TO SIMPLIFY TEST REPORTS AND ASSET MANAGEMENT

- WORLD'S FIRST VACUUM INTERRUPTER TEST SYSTEM CAPABLE OF PREDICTING REMAINING LIFE
- MAC-TS4 IS THE WORLD'S FIRST TEST SYSTEM CAPABLE OF TESTING VACUUM INTERRUPTERS IN BOTH THE SHOP AND FIELD
- BASED ON SAME OEM LEAK-RATE TEST PERFORMED AT THE FACTORY
- SYSTEM DOES CALCULATIONS BASED ON MEASUREMENTS OF 3,000 VACUUM INTERRUPTERS

13765 BETA ROAD | FARMERS BRANCH, TEXAS 75244 | [INFO@VACUUMINTERRUPTERSINC.COM](mailto:INFO@VACUUMINTERRUPTERSINC.COM)



**214-442-5877**  
[VacuumInterruptersInc.com](http://VacuumInterruptersInc.com)



# Magnetron Atmospheric Condition (MAC) Analysis

## MAC-TS4

### SPECIFICATIONS

**Type:** MAC-TS4

**Physical Specifications:** 16.9" × 12.6" × 9.8" (430mm × 320mm × 250mm) Weight: 28.4 lb (12.9Kg)

**Input Power:** 120V AC 50/60Hz (standard), 230V AC 50/60Hz (optional)

**Measure Range:**  $1 \times 10^{-5}$  Pa ~  $1 \times 10^{-1}$  Pa

**Measure Accuracy:** <10% of the reading

**Display:** Back-lit LCD screen (320 × 240 pixels); viewable in bright sunlight and low light conditions

**Printer:** Built-in 2.2-in. wide thermal printer

**Internal Test Record Storage:** Stores up to 500 test results

**Computer Interface:** One USB interface

**Computer Software:** Windows®-based software included with purchase price

**Certifications:** CE certified

**Environment:** Operating: -10°C to +50°C (+15°F to +122°F)

**Humidity:** 85% Rh @ 40°C (104°F) non-condensing

**Altitude:** 2,000 M (6,562 ft) to full safety specifications

**Cables:** Furnished with full set of test leads (including high-voltage output cable, signal input cable, magnetic coil output cable, 20-ft ground cable, and USB cable)

**Options:** Various-sized fixed coils

**Warranty:** One year on parts and labor



### STANDARD FEATURES

- Lightweight, portable tester
- Compatible with fixed or flexible magnetic field coils (one flex coil included in purchase price)
- Easy and safe to operate
- Graphical LCD display
- PC software allows user to control MAC-TS4 operation, download stored test results, and generate test reports
- Field or shop use



US PATENT NO. 9,031,795 B1

13765 BETA ROAD | FARMERS BRANCH, TEXAS 75244 | INFO@VACUUMINTERRUPTERSINC.COM



**214-442-5877**  
**www.VacuumInterruptersInc.com**

